Section 1: Product & Company Identification

NAPA/CRC® Brakleen® Brake Parts Cleaner - Non-chlorinated (aerosol) **Product Name:**

Product Number (s): 091847

Product Use: Brake parts cleaner

Manufacturer / Supplier Contact Information:

In United States: In Canada: In Mexico: CRC Industries, Inc. CRC Canada Co. **CRC Industries Mexico**

2-1246 Lorimar Drive Av. Benito Juárez 4055 G 885 Louis Drive Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

www.crcindustries.com www.crc-canada.ca San Luís Potosí, SLP CP 78394

1-215-674-4300 (General) 1-905-670-2291 www.crc-mexico.com 52-444-824-1666

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

24-Hr Emergency - CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Harmful or Fatal if Swallowed. May Cause Blindness if Swallowed.

Vapor Harmful. Eye and Skin Irritant. Contents Under Pressure. Appearance & Odor: Clear liquid; solvent odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: Moderate eye irritant. Exposure can cause irritation including stinging, tearing, redness, blurred vision,

and swelling of the eyes.

Moderate skin irritant. Prolonged or repeated contact may dry the skin. Symptoms may include

redness, burning, drying and cracking of the skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe

handling and use.

INHALATION: Breathing large amounts of this material may be harmful. Symptoms include irritation of the nose and

throat and central nervous system excitation (giddiness), followed by CNS depression (dizziness,

drowsiness, weakness, headache, nausea, unconsciousness).

INGESTION: Swallowing small amounts is not likely to cause harmful effects. May cause stomach or intestinal upset.

Swallowing larger amounts may be harmful as this material may be aspirated into the lungs during

swallowing or vomiting. This results in lung inflammation and other lung injury.

CHRONIC EFFECTS: Overexposure to methanol may lead to visual impairment.

TARGET ORGANS: liver, kidneys, blood, central nervous system, eyes

Medical Conditions Aggravated by Exposure: skin sensitivities, lung conditions, central nervous system conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): 091847

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Methanol	67-56-1	40 – 50
Toluene	108-88-3	15 – 25
Heptane	142-82-5 / 64742-49-0	15 – 25
Acetone	67-64-1	5 – 15
Carbon dioxide	124-38-9	5 – 10

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Seek medical attention. Do NOT induce vomiting unless instructed by medical personnel. Have

victim drink a glass of water if conscious.

Note to Physicians: This material is an aspiration hazard. This material (or a component) has produced hyperglycemia

and ketosis following substantial ingestion. Inhalation of high concentrations of this material may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This product contains methanol. The metabolites of methanol

can cause metabolic acidosis, visual disturbances and blindness.

Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: This product is extremely flammable in accordance with aerosol flammability definitions.

(See 16 CFR 1500.3(c)(6)).

Flash Point: 0°F / -18°C (TCC) Upper Explosive Limit: ND Autoignition Temperature: 725°F / 385°C Lower Explosive Limit: ND

Fire and Explosion Data:

Suitable Extinguishing Media: Dry chemical, carbon dioxide, alcohol-resistant foam, Class B extinguishers

Products of Combustion: Oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors

may accumulate in a confined space and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

Product Number (s): 091847

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Eliminate all sources of ignition. Dike area to contain spill. Ventilate the area

with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used

absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Do not use near potential sources of ignition. Do not use on energized equipment. Use with

adequate ventilation. Avoid contact with skin and eyes. Avoid inhaling vapors. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product

use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F /

49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	C	SHA	AC	GIH	0	THER	
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Methanol	200	NE	200	250 (s)	NE		ppm
Toluene	200	300 (c)	20	NE	NE		ppm
Heptane	500	NE	400	500	NE		ppm
Acetone	1000	NE	500	750	NE		ppm
Carbon dioxide	5000	30000(v)	5000	30000	NE		ppm
N.E. – Not Established (c) – ceiling		(s) –	skin (v) – vaca	ted		

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Product Number (s): 091847

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, PVA, or neoprene. Also, use full protective clothing if

there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: clear
Odor: solvent
Odor Threshold: ND
Specific Gravity: 0.782
Initial Boiling Point: 132°F / 56°C

Freezing Point: ND Vapor Pressure: ND

Vapor Density: > 1 (air = 1)

Evaporation Rate: fast

Solubility: slightly soluble in water Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 84.0 g/L: 657.2 lbs./gal: 5.5

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Sources of ignition; temperature extremes

Incompatible Materials: Acids, alkalis, reducing agents, strong oxidizing agents, hypochlorites, peroxides, reactive

metals such as aluminum and magnesium, sodium, zinc

Hazardous Decomposition Products: Oxides of carbon, various hydrocarbons

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Methanol	5600 mg/kg	15,800 mg/kg	81,000 mg/m ³ /14H
Toluene	636 mg/kg	14,100 μL/kg	49 g/m ³ /4H
Heptane	No data	No data	103 g/m ³ /4H
Acetone	5800 mg/kg	No data	50,100 mg/m ³ /8H
Carbon dioxide	No data	No data	470,000 ppm/30M

Product Number (s): 091847

Chronic Toxicity:

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	Carcinogen	<u>Irritant</u>	Sensitizer
Methanol	No	No	No	E & S (moderate)	Unknown
Toluene	No	No	No	E, S, R (mild)	Unknown
Heptane isomers	No	No	No	E & R (mild) / S (moderate)	Unknown
Acetone	No	No	No	E & S (moderate) / R (mild)	Yes
Carbon dioxide	No	No	No	No	No

E – Eve	S – Skin	R - Respiratory

Reproductive Toxicity: No information available Teratogenicity: No information available Mutagenicity: No information available Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Acetone - 48H LC50 Daphnia: 10 mg/l Ecotoxicity: Persistence / Degradability: No information available Bioaccumulation / Accumulation: No information available Mobility in Environment: No information available

Section 13: Disposal Considerations

The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with Waste Classification:

the following potential waste code(s): D001, F005. (See 40 CFR Part 261.20 - 261.33) Aerosol containers should be fully emptied and depressurized before disposal. Empty aerosol containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): Consumer Commodity, ORM-D

ICAO/IATA (air): Consumer Commodity, ID8000, 9

Aerosols, UN1950, 2.1, Limited Quantity IMO/IMDG (water):

Special Provisions: None

Product Number (s): 091847

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Acetone (5000 lbs), Toluene (1000 lbs),

Methanol (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No
Release of Pressure Yes
Acute Health Hazard Yes
Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements

of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of

1986 and 40 CFR Part 372:

Toluene (< 20%), Methanol (< 46%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Toluene, Methanol

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of

California to cause cancer, birth defects or other reproductive harm: Toluene

<u>Consumer Products VOC Regulations</u>: This product does not comply with Consumer Products VOC regulations and

cannot be used in California, Connecticut, Delaware, The District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New Hampshire, New York, Ohio, Pennsylvania, Rhode Island, and parts of Virginia.

State Right to Know:

New Jersey: 67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5 Pennsylvania: 67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5 Massachusetts: 67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5 Rhode Island: 67-64-1, 108-88-3, 67-56-1, 124-38-9, 142-82-5

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D1A, D2A, D2B

Product Number (s): 091847

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the

Council of 27 January 2003. This product does not contain any of the restricted substances as


listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)			
Health:	2		
Flammability:	3		
Reactivity:	0		
PPE:	В		

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 483A Revision Date: 10/06/2011

Changes since last revision: formula change

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association

ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization

lbs./gal: pounds per gallon LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup
PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System