

MATERIAL SAFETY DATA SHEET

Page 1

FOR COATING, RESINS, AND RELATED MATERIALS

Date of Preparation- 3/30/07 Prepared by- CASEY TURNER

Manufacturer: ROSE TALBERT PAINT COMPANY
Address : 901 FRINK STREET
CAYCE, SC 29033

Telephone#: (803) 796-0324 Night:
Emergency#: (800) 255-3924 Night:

SECTION I PRODUCT IDENTIFICATION

Manufacturer's Code Identification: 00600
Product Class: INT LATEX FLAT PAINT
Trade Name: PREMIUM VELVET VINYL LATEX FLAT- WHITE

MIS Information: Health- 01 Flammability- 1
Reactivity- 0 Personal Protective Equipment- E
HAZARD INDEX: 4= Severe 3= Serious 2= Moderate 1= Slight 0= Least
= 3

Safety Glasses, Gloves, & Dust Respirator

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT		% BY	ACGIH	OSHA	VAPOR
MATERIAL DESCRIPTION	CAS#	WT.	TLV (TWA)	PEL	PRESSURE
REF#			PPM	PPM OTHER	LIMITS
16 ETHYLENE GLYCOL	/107-21-1	/ 2.05	/ 50.00/	40.00/	3.2 .08
19 TITANIUM DIOXIDE	/13463-67-7	/ 12.49	/NOT EST/	NOT EST/	
	% LEAD		.00		
	% CHROMATE		.00		

This product contains no reported carcinogens or suspected carcinogens.

This product contains pigments which may become a dust nuisance when removed by abrasive blasting, sanding, or grinding.

SECTION III PHYSICAL DATA

Boiling Range: High- 387.0 F Low- N/A
Vapor Pressure: .08 MMHG @68 F
Vapor Density: Heavier Than Air
Evaporation Rate: Slower than Butyl Acetate
Weight per Gallon: 11.2
% Volatile by Volume: 64.81
% Volatile by Weight: 48.41
GOC: .824
Physical State: LIQUID
Appearance: N/A
Odor: N/A
Odor Threshold: N/A
pH: N/A
Freezing Point: N/A
Water Solubility: N/A
Coefficient of Water/Oil Distribution: N/A

00600

ROSE TALBERT PAINT COMPANY

MATERIAL SAFETY DATA SHEET

Page 2

PREMIUM VELVET VINYL LATEX FLAT- WHITE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flammability Classification : DOT- @
Lowest Flashpoint TCC ^ Lower Explosion Level(LEL) [

Flammability Classification: Class 3B DOT: Not Regulated

Lowest Flashpoint TCC: 240.0 F
Explosion Level: Lower- 3.2 Upper- 15.3

Upper Flammability Limit: N/A
Auto Ignition Temperature: N/A

EXTINGUISHING MEDIA

Use CO2, Dry Chemical, or Foam extinguisher.

The National Fire Protection Association Class B extinguisher is designed to extinguish NFPA class 1B flammable liquid fires.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed container may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near container (even empty) because product (even residue) may ignite explosively.

HEAT PROTECTION PROCEDURES

Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture.

SECTION V HEALTH HAZARD DATA

EFFECTS OF EXCESSIVE OVEREXPOSURE

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

Based on the presence of components (20) this product may cause nose and throat irritation.

Based on the presence of components (20) this product can be irritating to the eyes.

Based on the presence of components (20) this product may cause skin irritation and drying/defatting or cracking, and dermatitis on repeated or prolonged exposure to the skin.

FIRST AID

EYE CONTACT: Flush with luke warm water for 15 minutes. Seek physician immediately.

00600

ROSE TALBERT PAINT COMPANY
MATERIAL SAFETY DATA SHEET

Page 3

PREMIUM VELVET VINYL LATEX FLAT- WHITE

SKIN CONTACT: Flush wash with copious amounts of luke warm water. Remove contaminated clothing promptly. Contact a physician immediately.

INHALATION: Remove exposed individual to fresh air. Restore breathing if required. Contact a physician immediately.

INGESTION: Rinse mouth immediately. Give exposed individual 6 to 8 ounces of liquid. (Never give anything by mouth to an unconscious person.) Do NOT induce vomiting unless advised by a physician. Contact a physician immediately.

SECTION VI REACTIVITY DATA

CONDITIONS TO AVOID

Avoid exposure to sparks, open flame, hot surfaces, and all sources of heat and ignition.

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain carbon monoxide, carbon dioxide, and oxides of nitrogen.

INCOMPATIBILITY (Materials to Avoid)

This product is incompatible with strong acids.

STABILITY

This product is stable.

HAZARDOUS POLYMERIZATION

Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Stay upwind and away from spill unless wearing appropriate protective equipment. Stop and/or contain discharge if it may be done safely. Keep all sources of ignition away. Ventilate area of spill. Use non-sparking tools for cleanup. Cover with inert material to reduce fumes. Keep out of drains, sewers, or waterways. Contact fire authorities. Notify local health and pollution control agencies. Call spill response teams if large spill.

WASTE DISPOSAL METHOD

DO NOT FLUSH TO SEWER, WATERSHED, OR WATERWAY.

Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

SECTION VIII SAFE HANDLING AND USE INFORMATION

DISCRETION ADVISED

Rose Talbert Paint Company takes no responsibility for determining what measures are required for personal protection in any specific application. The general information given should be used with discretion.

PROTECTIVE GLOVES

Required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact.

PROTECTIVE EYEWEAR

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes.

Eyewash stations and safety showers should be readily available in use and handling areas.

Use safety eyewear with perforated sideshields.
RESPIRATORY PROTECTION

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) air line type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

VENTILATION

Use ventilation as required to control vapor concentrations. Avoid prolonged or repeated breathing of vapors. If exposure exceeds TLV, use a NIOSH-approved respirator to prevent overexposure. Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV of the most hazardous ingredient in Section II below acceptable limit, LEL in Section IV below stated limit, and to remove decomposition products during welding or flame cutting on surfaces coated with this product.

HYGIENIC PRACTICES

WASH HANDS THOROUGHLY BEFORE EATING AND USING WASHROOM.

Remove contaminated clothing immediately and do not wear it until it has been properly laundered.

SECTION IX SPECIAL PRECAUTIONS

HANDLING AND STORING PRECAUTIONS

Keep product containers cool, dry, and away from sources of ignition. Use and store this product with adequate ventilation. Do NOT smoke in storage areas.

Personnel should avoid inhalation of vapors. Personal contact with the product should be avoided. Should contact be made, remove saturated clothing and flush affected skin areas with water. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this sheet must be observed.

NOTICE - Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SECTION X Section 313 Toxic Chemicals

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

Chemical	CAS Number	Weight %
ETHYLENE GLYCOL	107-21-1	2.05

00600

ROSE TALBERT PAINT COMPANY
MATERIAL SAFETY DATA SHEET
PREMIUM VELVET VINYL LATEX FLAT- WHITE

Page 5

THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED
FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES AND
IS BELIEVED TO BE RELIABLE. THIS DATA IS NOT TO BE TAKEN
AS A WARRANTY OR REPRESENTATION FOR WHICH ROSE TALBERT
PAINT COMPANY ASSUMES LEGAL RESPONSIBILITY.