MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174								
IDENTITY AND D								
		HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B						
		DOT Hazard Classification: ORM-D						
		Identity (trade name as used on label):						
Address: St. Joseph, MO 64502		STAINLESS STEEL CLEANER						
Phone: (816) 233-1321 ext 2303 or http://www.hillyard.com		MSDS Number: 142 Revision- 10						
			Information Calls: (770)422-2071					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Date Prepared: 03/29/96 Prepared By: LF							.F	
SECTION 1 - MATERIAL	. IDENTII	FICATION	ON AND INFOR	MATION				
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES			CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)				III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ISOBUTANE / PROPANE BLEND			75-28-5	No	800	800	d	
			74-98-6	No	1000	1000	d	
PETROLEUM SOLVENT			64742-54-7	No	5mg/m3	5mg/m3	d	
PETROLEUM DISTILLATE			8052-41-3	No	100	100	d	
			0002 11 0	-110	100	100	- u	
							 	
							l	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS								
			pecific Gravity (H2O=1): Concentrate Only = 0.908					
			/apor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
			Evaporation Rate (= 1): N/E					
			Vater Reactive: No					
Appearance and Odor: White foam with light lemon fragrance.								
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA								
FLAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume:								
(aerosols) NON-FLAMMABLE			N/E	% LEL		-	.: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A	F							
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.								
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.								
SECTION 4 - REACTIVITY HAZARD DATA								
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR								
Incompatibility (Mat. to avoid): Strong oxidants. Conditions to Avoid: Open flame, welding arcs, heat.								
Hazardous Decomposition Products: CO, CO2.								
SECTION 5 - HEALTH HAZARD DATA								
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS								
ACUTE EFFECTS:								
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.								
Eye Contact: Mild irritation. Skin Contact: May aggravate existing skin conditions. Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.								
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause headaches, dizziness and nausea.								
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.								
EMERGENCY FIRST AID PROCEDURES								
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.								
Skin Contact: Wash with soap and water. If irritated, seek medical attention.								
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.								
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.								
SECTION 6 - CONTROL AND PROTECTIVE MEASURES								
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in a positive pressure mode.								
Protective Gloves: Latex if skin easily irritated. Eye Protection: Safety glasses recommended.								
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.								
Other Protective Clothing & Equipment: None								
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.								
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE								
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO								
NOT FLUSH TO SEWER. Waste Disposal Methods: Agreed cans when vented to atmospheric pressure through normal use, pose no disposal hazard.								
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.								
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.								
,								
We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.								

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

*** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains

THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.