MATERIAL SAFETY DATA SHEET This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This MSDS complies with OSHA'S Hazard Commu	unicatior	n Standard 29 CFR 191	0.1200 an	d OSHA Form	n 174	
IDENTITY AND MANUF	ACTU	RER'S INFORMATIO	ON			
FPA Rating: Health-1; Flammability-4; Reactivity-0; Special HMIS Rating: Health-1; Flammability-4; Reactivity-0; Personal Protection-B						
Manufactured For: Hillyard Industries, Inc.	DOT Hazard Classification: ORM-D					
Address: 302 N. 4 th Street	Identity (trade name as used on label):					
Address: St. Joseph, MO 64501	GUM-GO Part #HIL0103054					
Phone: (816)-233-1321 ext. 8285 or http://www.hillyard.com	MSDS Number: A00183 Revision- 5					
EMERGENCY RESPONSE NUMBER: Chemtrec 1-800-424-9300	Date Prepared: 04/23/07 Prepared By: ES/CH/IB					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	III LIST	(ppm)	TLV (ppm)	Ref. Source **
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
		74-30-0	INU	1000	1000	u
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS						
Description Specific Gravity (H2O=1): Concentrate Only = 0.54						
Vapor Pressure: PSIG @ 70°F (Aerosols): 70-80	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Density (Air = 1): Concentrate only = greater than 1.5	Evaporation Rate (BuAc = 1): Faster					
Solubility in Water: Negible Water Reactive: No						
Appearance and Odor: Clear, odorless spray.			T A			
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) 44-48 Auto Ignition Temperature Flammability Limits in Air by % in Volume:						
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) 44-48 inches, flashback to tip under partial actuator depression: Categorized:	A	uto Ignition Temperatu N/E		LEL: 2.0		% in Volume: EL: 10.0
EXTREMELY FLAMMABLE		IN/E	70	LEL. 2.0	70 UI	EL. 10.0
FLASH POINT AND METHOD USED (non-aerosols): -156 °F				EXTINGU	ISHER MEDI	∆ : Foam_dry
FLASH POINT AND METHOD USED (non-aerosols): -156 °F EXTINGUISHER MEDIA: Foam, dry Chemical, carbon dioxide.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - READ						
STABILITY [X] STABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
				<u> </u>		-
Incompatibility (Mat. to avoid): Strong oxidizing agents. Conditions to Avoid: Open flame, welding arcs, heat, sparks, or any source of ignition. Hazardous Decomposition Products: CO, CO2.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS						
ACUTE EFFECTS:						
Inhalation: Product is an asphyxiant at very high concentrations. Excessive inhalation of vapors can be harmful and may cause headache,						
disorientation, rapid respiration, nausea, anesthetic effects and possible unconsciousness. Vapors are heavier than air and displace oxygen						
required for breathing. Abusive, excessive inhalation of vapors can result in asphysia (death.)						
Eye Contact: May cause burns and frostbite. Skin Contact: May cause burns and frostbite.						
Ingestion: Unlikely route of exposure. Gas under normal (usual) circumstances.						
CHRONIC EFFECTS: Unknown.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush immediately with fresh water for at least 15 minutes while holding eyelids open. Remove contact lenses if worn. Seek						
medical attention immediately.						
Skin Contact: Treat burned or frostbitten skin by flushing or immersing affected areas in lukewarm water. If skin is not burned, keep warm and						
stimulate circulation with massage. Seek medical attention immediately.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Give oxygen.						
Ingestion: Unlikely route of exposure.	nour utt	ention. One exygen				
SECTION 6 - CONTROL A						
Respiratory Protection (specify type): If vapor concentration excee	eds TL	V, use respirator app	roved by	NIOSH to b	e used in a	positive
pressure mode.						
Protective Gloves: Rubber gloves recommended.		Protection: Safety	glasses	recommende	ed.	
Ventilation Requirements: Adequate ventilation to keep vapor cond	centrati	on below TLV.				
Other Protective Clothing & Equipment: Self-contained respirator	should	be available for non	-routine a	and emerger	ncy situation	S.
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS	-			5		
Steps To Be Taken If Material Is Spilled Or Released: Isolate haz	-			l ignition sou	Irces Ventil	ate area to
				i iginitori sot		
disperse vapors. If liquid gas has not ignited, disperse with water or by flooding. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Avoid						
contact with skin or eyes.					_	-
We believe the statements, technical information and recommendations conta						
** Chemical Listed as Carcinogen or Potential Carcinogen. [a]	NTP [b]	IARC Monograph [c] C	SHA [d] N	lot Listed [e] A	Animal Data O	nly